

Gainscha

Reliable and Innovative



2" Wide GS-2208D



SURPASS SERIES

--2inch Thermal Label and Wristband Printer

KEY FEATURES

Dedicate for retail, healthcare label and wristband printing Easy to install print media, without need ribbon Strong compatibility to software, improve work efficiency



SIMPLE TO USE

HIGH PERFORMANCE

COST EFFECTIVE



SURPASS SERIES -

2"Desktop Direct Thermal Label Printer

PRINTER MODEL	GS-2208D
Resolution	8dots/mm (203DPI)
Printing Method	Direct Thermal
Max. print speed	203.2mm (8")/second
Max. print width	54mm (2.13")
Memory RAM	64MB SDRAM
Memory ROM	32MB Flash Memory(128MB Flash Memory Option)
Interface	USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard Internal Ethernet 10/100Mbps Internal Bluetooth 4.0 (factory option) Internal Wi-Fi (factory option)
Power	Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A, 60W
Internal fonts	8 alpha-numeric bitmap fonts True type font engine (need download scalable font file)
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix
Rotation	Font and barcode support 0, 90, 180, 270 degree
Printer language	Compatible to EPL, EPL 2, ZPL, ZPL II, DPL, TSPL
Physical dimension	129mm(W)x165.3mm(H)x244.3mm(D)
Weight	1.3Kg



Enclosure
ABS plastic

Certification
FCC, CE, CCC, BIS, CB

User options
External roll mount

Environment concern
Comply with RoHS, REACH, WEEE

Accessories
Windows labeling software CD disk/Quick start guide/USB cable/Power cord/External universal switching power supply

Environment condition
Operation: 5~40°C, 25~85% non-condensing
Storage: -40~60°C, 10~90% non-condensing



Applications

- Medical
- Entertainment
- Retail
- Pet wristband
- Restaurant

